

BATTERY POWERED WIRELESS IOT SOLUTIONS
MONITOR PREMISES AND ASSETS 24/7

LRS30100 LoRaWAN® INDOOR ENVIRONMENTAL SENSOR




Product Features

- LRS30100 LoRaWAN® indoor environmental sensor provides a simply efficient solution for monitoring Ambient Temperature & Humidity, Carbon Dioxide, TVOC, Ambient Light and Motion
- Long Battery Life
- Compliant with LoRaWAN® standard
- Configurable data upload interval and alert settings
- Applications: Indoor Air Quality Monitoring for Office, Shop, Mall, School, etc....

Performance Characteristics

Input Power	3 x 3.6V AA Size ER14505 Lithium Battery
Battery Life	Up to 3 years ⁽¹⁾ Up to 5 years ⁽¹⁾ (model with temperature and humidity only)
Measurement period	1 min
Data upload interval (heartbeat)	Configurable (default: 10 mins)
On-device alert detection	Yes, exceeds alert thresholds (temperature/humidity/CO2/TVOC)
Temperature	Measurement range: -20°C to 60°C, Resolution: 0.1°C Accuracy: ±0.6°C (-20°C to -10°C), ±0.4°C (-10°C to 5°C) and ±0.2°C (5°C to 60°C)
Humidity	Measurement range: 0 to 100% RH, Resolution: 0.5% Accuracy: ±3%RH (5-20% RH), ±2%RH (20-80%RH) and ±3%RH (80-95%RH)
TVOC	Measurement range: 0 – 10,000ppb, 1 - 2,000µg/m ³ Resolution: 1µg/m ³ , Accuracy: (±20µg/m ³ +15%) at 1 to 1000µg/m ³
Carbon Dioxide (CO ₂)	Measurement range: 400ppm-5,000ppm Resolution: 1ppm, Accuracy: ±50ppm ± 3% reading
Motion	Detection Angle: <= 100 deg Detection Range: 3m
Ambient Light	Measurement range: 4 - 2000 Lux Resolution: 1 Lux Accuracy: +/- 15 %

(1) Based on 10 mins heartbeat interval



Wireless Characteristics

Wireless Connectivity	LoRaWAN® 1.0.3 EU863-870, US902-928, AU915-928, AS923
Transmit Power	EU868, AS923: +16dBm US915, AU915: +20dBm
Sensitivity	Max. -137dBm
Data Transfer Rate	0.3kbps – 50kbps
LoRaWAN® Features	ABP / OTAA, Class A End-device
Antenna Type	Built-in Antenna
Security	AES-CTR (LoRaWAN End-to-End Encryption) AES-CMAC (Data Integrity Protection)

Physical Characteristics

Dimension	L 89mm x W 89mm x H 32mm (TBC)
Weight	Approx. 165g (TBC)
Operating Temperature	0°C to 50°C
Operating Relative Humidity	0% to 100% RH (non-condensing)
Storage Temperature	-10°C to 60°C
Storage Humidity Range	0% to 100% RH (non-condensing)
Warranty Period	1 Year

Ordering Information

Partnumber	Sensor Features
LRS30100-0000-000a	Temperature, Humidity
LRS30100-0000-110a	Temperature, Humidity, Light, Motion
LRS30100-C000-110a	Temperature, Humidity, CO2, Light, Motion
LRS30100-CV00-110a	Temperature, Humidity, CO2, TVOC, Light, Motion

Nomenclature for suffix:

LRS30100-CV00-110a

↑
0 – AS923, 1 – EU868, 2 – US915, 3 – AU915